This listing will replace all prior versions, and listings, of claims in the Application:

What is claimed is:

- (Original) A mobile catalyst injection system comprising:
 - a transportable platform;
- a catalyst reservoir coupled to the platform and adapted to be coupled to an fluid catalyst cracking unit; and
- a flow control device coupled to an outlet of the reservoir and adapted to control the flow of catalyst through the outlet port.
- 2. (Original) The system of claim 1, wherein the platform is a trailer.
- (Original) The system of claim 1, wherein the platform is a container.
- 4. (Original) The system of claim 1, wherein the platform is a railroad car.
- 5. (Original) The system of claim 1, wherein the platform is a pallet.
- 6. (Original) The system of claim 1, wherein the platform is a barge.
- (Original) The system of claim 1 further comprising: a generator coupled to the platform.
- (Original) The system of claim 1 further comprising:
- a controller coupled to the platform and flow control device for controlling the catalyst dispensed from the catalyst reservoir.

- 9. (Currently amended) The system of claim 1 further comprising:
- a pressure control system coupled to the platform and the catalyst reservoir for controlling pressure with in within the catalyst reservoir.
- (Original) The system of claim 1, wherein the catalyst reservoir is movable relative to the platform.
- 11. (Original) The system of claim 1 further comprising a plurality of load cells disposed between the catalyst reservoir and the platform.
- (Original) The system of claim 1 further comprising sensor adapted to detect a
 metric indicative of catalyst dispensed from the catalyst reservoir.
- 13. (Original) The system of claim 1, wherein the catalyst reservoir further comprises:
 - a plurality of compartments; and
 - a plenum disposed in the catalyst reservoir and coupling the compartments.
- 14. (Original) The system of claim 13, wherein at least two of the plurality of compartments are substantially equal in volume.
- 15. (Original) The system of claim 13, wherein at least two of the plurality of compartments are substantially unequal in volume.
- (Original) The system of claim 13, wherein at least one of the plurality of compartments has an adjustable volume.
- 17. (Original) The system of claim 1 further comprising a second catalyst reservoir coupled to the platform and adapted to be coupled to the fluid catalyst cracking unit.

- 18. (Original) A mobile catalyst injection system comprising:
 - a trailer:
- a catalyst reservoir coupled to the trailer and adapted to be coupled to an fluid catalyst cracking unit;
 - a pressure control system coupled to the trailer and catalyst reservoir;
 - a generator coupled to the pressure control system; and
- a flow control device coupled to an outlet of the reservoir and adapted to control the flow of catalyst through the outlet port.
- 19. (Original) The system of claim 18, wherein the catalyst reservoir further comprises:
 - a plurality of compartments; and
 - a plenum disposed in the catalyst reservoir and coupling the compartments.
- (Original) The system of claim 19, wherein at least one of the plurality of compartments has an adjustable volume.
- 21. (Currently amended) The system of claim 18 further comprising:
- a second catalyst reservoir coupled to the platform <u>trailer</u> and pressure control system.
- 22. (Currently amended) A mobile catalyst injection system comprising:
 - a container:
- a catalyst reservoir coupled to the container and adapted to be coupled to an fluid catalyst cracking unit:
 - a pressure control system coupled to the trailer container and catalyst reservoir;
 - a generator coupled to the pressure control system; and
- a flow control device coupled to an outlet of the reservoir and adapted to control the flow of catalyst through the outlet port.

- 23. (Original) The system of claim 22, wherein the catalyst reservoir further comprises:
 - a plurality of compartments; and
 - a plenum disposed in the catalyst reservoir and coupling the compartments.
- 24. (Original) The system of claim 23, wherein at least one of the plurality of compartments has an adjustable volume.
- (Currently amended) The system of claim 22 further comprising:
- a second catalyst reservoir coupled to the platform <u>a container</u> and pressure control system.
- 26. (Currently amended) A method for process control in a fluid catalytic cracking system, comprising:

processing oil in a fluid catalytic cracking system having a one or more hard piped catalytic injection systems;

transporting a mobile catalyst injection <u>system</u> to the fluid catalytic cracking system;

coupling the mobile catalyst injection system to the fluid catalytic cracking system; and

injecting catalyst from the mobile catalyst injection <u>system</u> into the fluid catalytic cracking system.

- 27. (Original) The method of claim 26, wherein the step of transporting further comprises moving the mobile catalyst injection system by at least one of road, land, sea or air.
- 28. (Original) The method of claim 26 further comprising:

identifying a need for a catalyst needed in addition to catalysts being dispensed by the one or more hard piped catalytic injection systems.

- 29. (Original) The method of claim 28, wherein the step of transporting is in response to the identified need
- 30. (Original) The method of claim 29, wherein the step of injecting occurs within at least 1 hour after the completion of the transporting step.
- (Currently amended) The method of claim 26 further comprising: storing catalyst in a first compartment of the <u>mobile catalyst</u> injection system; and storing catalyst in a second compartment of the <u>mobile catalyst</u> injection system.
- 32. The method of claim 31 further comprising adjusting a ratio of volume between the first and second compartments.
- (Original) The method of claim 31 further comprising pressurizing a plenum common to the first and second compartments.
- 34. (Original) The method of claim 31, wherein the step of injecting further comprises:

dispensing at least two catalysts simultaneously from the two respective compartments.

35. (Original) The method of claim 31, wherein the step of injecting further comprises:

dispensing at least two catalysts sequentially from the two respective compartments.